



IMT products are:

- Maintenance free
- Safety
- Environmental friendly

Aquarius

Control Box Helideck

Specification/Technical Data

- | | |
|------------------------------------|---|
| Ambient temp. range: | -20°C-> +40°C. |
| Ingress protection: | IP66 |
| Enclosure type*: | EJB 15A |
| Dimensions*: | 580x428x273 |
| Material: | Sea water resistant aluminium |
| Finish: | polyester powder coating RAL7035. |
| Incoming voltage: | 24Vdc or 230Vac (other voltages on request) |
| Indication lamps on cover: | <ul style="list-style-type: none"> - Power on - Main light A on. - Main light B on. (depending on configuration) - Repeater light A on. (depending on configuration) - Repeater light B on. (depending on configuration) - Dimmer mode on - Common system alarm. |
| Operator buttons on cover; | <ul style="list-style-type: none"> - Lamp test. - Dimmer - System manual-off-remote. |
| Entries : | M25 |
| Standard system inputs. | <ul style="list-style-type: none"> - FSG input. (on/off switching of the system) - Dimmer input. (for remote dimming facility) - ESD input (for immediate off switching of the system in case of an ESD) |
| Standard system volt free outputs: | <ul style="list-style-type: none"> - System on. - Dimmer on. - Common system alarm. |

Certification Details:

- | | |
|----------------------|---------------------------------|
| ATEX Classification: | Group II, Category 2, Gas |
| Area Classification: | Category 2 (Zone 1 and 21) |
| Certificate: | INERIS 01ATEX0025 |
| Marking: | Ex II 2GD Exd(i) IIB, Ex tD A21 |



*Photos and dimensions may differ from reality.